




GO TO PRODUCT



General data

Product group:	ICT / FCT (in-circuit test and function test)
Sub-product group:	Rotating test probes
Series:	GKS-713
Grid:	4.5 mm [177 mil]
Contacting from:	
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	No
Type of test probe connection:	Plug
Adjustable installation height:	No
Non-rotating:	No
Continuous plunger:	ø1,3 x 10,0
Compatible connector(s):	SE-503
Compatible receptacle(s):	KS-713
Min. temperature:	-40 °C [-40 °F]
Max. temperature:	80 °C [176 °F]
RoHS-compliant:	Yes

Tip style data

Tip style:	57 30° 3-edged chisel, self-cleaning, special length
Tip diameter:	2.25 mm [.088 in]
Tip style surface:	R rhodium
Tip style material:	2 steel

Electrical data

Current load capacity / rated current:	5 A
Current rating, connection on plunger:	8 A
Typical resistance (Ri):	30 mOhm
Typical resistance (Ri), connection on plunger:	10 mOhm

Mechanical data

Total length:	40 mm [1.57 in]
Barrel diameter:	2.65 mm [.104 in]
Maximum stroke:	5 mm [.196 in]
Spring pre-load:	1.05 N [3.77 ozf]
Collar height:	7
Spring force at working stroke:	3 N [10.7 ozf]
Recommended working stroke:	4 mm [.157 in]

Test Probe


GKS-713 257 225 R 3007

Item GKS-713-0018



ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 11/25_GB

Learn more about
ICT/FCT Test probes



ingun.com

ICT/FCT TEST PROBES