

Reinforcement set FB-VSL-KIT-NDH-ATSMA15

Item 115006



GO TO PRODUCT

ingun[®]
Partner for Future Technology

- For installation on the pressure frame plate (NHP)
- Recommended for customisations with more than 300 test probes or a force greater than 500 N
- The scope of delivery includes one strip with fixing material in each case

Application

For reinforcing the pressure frame plate (NHP) to prevent deflection due to high forces resulting from customisation.



General data

Product group:
Series:
Type:
Version:
Accessory type:
Scope of delivery:
Material:
Width:
Height:
Weight:
Min. temperature:
Max. temperature:
RoHS-compliant:

Functional units
FB-ATSMAXx
Reinforcement bar for pressure plate (NHP)
Set including installation accessories
Additional function
1 x reinforcement bar
1.0037, galvanised
10 mm [.393 in]
20 mm [.787 in]
0.8 kg [1.76 lbs]
10 °C [50 °F]
60 °C [140 °F]
Yes

Compatible with

Exchangeable kits version:
MA exchangeable kits (ATS MA):

No RF
ATS MA15

Technical data

Installation:
Length:
Outer dimensions (WxDxH): 10 x 474 x 20 mm [.393 x 18.6 x .787 in]
Thread bush M4
474 mm [18.6 in]

Reinforcement set

FB-VSL-KIT-NDH-ATSMA15

Item 115006



GO TO PRODUCT

ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162

78467, Constance, Germany

Phone +49 7531 8105-0

Customer hotline +49 7531 8105-888

Fax +49 7531 8105-65

info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 12/25_GB

2 / 2

ingun.com



Learn more about
MA functional units

FUNCTIONAL UNIT