





GO TO PRODUCT

- Robust, compact design for harsh ICT/FCT applications with limited space
- For optimum contact at the test points (e.g. pads, vias, and pins), various tip styles in different diameters and finishes, as well as various spring forces are available.

**General data**

Product group: ICT / FCT (in-circuit test and function test)
 Sub-product group: Short/robust GKS
 Series: GKS-003
 Grid: 3.18 mm [125 mil]
 Contacting from: Post
 Magnetic: Yes
 Installation type: Plug-in
 Quick-exchange system: Yes
 Adjustable installation height: No
 Non-rotating: No
 Compatible receptacle(s): KS-003
 Min. temperature: -40 °C [-40 °F]
 Max. temperature: 80 °C [176 °F]
 RoHS-compliant: Yes

Tip style data

Tip style: 02 flat
 Tip diameter: 1.27 mm [.05 in]
 Tip style surface: A gold
 Tip style material: 3 CuBe

Electrical data

Current load capacity / rated current: 8 A
 Typical resistance (R_i): 20 mOhm

Mechanical data

Total length: 33.1 mm [1.3 in]
 Barrel diameter: 2.03 mm [.079 in]
 Maximum stroke: 6.35 mm [.25 in]
 Spring pre-load: 0.49 N [1.76 ozf]
 Collar height: 00
 Spring force at working stroke: 1.2 N [4.31 ozf]
 Recommended working stroke: 4.4 mm [.173 in]


Test Probe GKS-003 302 127 A 1200

Item GKS-003-0022



GO TO PRODUCT

ingun[®]
Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 12/25_GB

2 / 2

Learn more about
ICT/FCT Test probes



ingun.com