






- Equipped with INGUN test probes
- Suitable for test fixtures with internal or external Pylon interface
- Consistently low contact resistances and replicable measured values
- High contact reliability and transmission quality
- Reliable transmission of high current signals

Application

Interface blocks (SB) are used to reliably transmit signals between test device and test system in internal and external Pylon interfaces. High-current blocks are suitable for the reliable transmission of high currents and hazardous voltages within the scope of their specification.

Signal transmission

The signal is transmitted via two opposing interface blocks, which are designed for a working distance of 15.1 ± 0.5 mm between their mounting surfaces.



General data

Product group:
Series:
Type:
Version:
Accessory type:
Component assembly:
Weight:
Min. temperature:
Max. temperature:
RoHS-compliant:

Interface blocks (SB)
SB-HS
High-current block
Device under test (DUT) side
Customising accessories
KT-254L3E02-30 (solder)
0.03 kg [.066 lbs]
-30 °C [-22 °F]
120 °C [248 °F]
Yes

Electrical data

Typical resistance (R_i) of one GKS: 5 mOhm

Compatible with

Compatible mating part 1:
MA exchangeable kits (ATS MA):

SB-T-HS-034-20A
ATS MAXX

Technical data

Working distance:	15,1 +/- 0,5 mm
Connection:	Solder cup
Number of poles:	34 (fixed positions)
Air distance (not wired):	3 mm [.118 in]
Max. current of one GKS:	20 A
Max. current of all GKS:	1.5 A
Max. voltage:	270 V
Max. power loss:	5 W
Min. line cross-section:	0.25 mm ² [.00038 in ²]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

