




GO TO PRODUCT

- Well-established test probes for contacting PCBs
- For optimal contact to the test points (e.g. pads, vias, and pins), various tip styles with various diameters and finishes are available.
- Various spring forces available as well as versions with stainless steel springs suitable for high temperatures
- Used for setting the optimum stroke conditions in the test fixture, various installation heights can be achieved by combining test probes and receptacles

INGUN SELECTION



General data

Product group: ICT / FCT (in-circuit test and function test)
 Sub-product group: Standard stroke test probe
 Series: GKS-075
 Grid: 1.91 mm [75.1 mil]
 Contacting from: Post
 Magnetic: Yes
 Installation type: Plug-in
 Quick-exchange system: Yes
 Adjustable installation height: No
 Non-rotating: No
 Compatible receptacle(s): KS-075
 Min. temperature: -40 °C [-40 °F]
 Max. temperature: 80 °C [176 °F]
 RoHS-compliant: Yes

ICT / FCT (in-circuit test and function test)
 Standard stroke test probe

Tip style data

Tip style: 03 inverse cone
 Tip diameter: 1.2 mm [.047 in]
 Tip style surface: A gold
 Tip style material: 3 CuBe

Electrical data

Current load capacity / rated current: 4 A
 Typical resistance (R_t): 20 mOhm

Mechanical data

Total length: 33.1 mm [1.3 in]
 Barrel diameter: 1.02 mm [.04 in]
 Maximum stroke: 6.35 mm [.25 in]
 Spring pre-load: 0.72 N [2.58 ozf]
 Collar height: 00
 Spring force at working stroke: 2 N [7.19 ozf]
 Recommended working stroke: 4.3 mm [.169 in]


Test Probe GKS-075 303 120 A 2000

Item GKS-075-0052



GO TO PRODUCT

ingun[®]
Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 12/25_GB

2 / 2

Learn more about
ICT/FCT Test probes



ingun.com