




GO TO PRODUCT



General data

Product group:
Sub-product group:
Series:
Grid:
Contacting from:
Magnetic:
Installation type:
Quick-exchange system:
Type of test probe connection:
Adjustable installation height:
Non-rotating:
Continuous plunger:
Compatible connector(s):
Compatible receptacle(s):
Min. temperature:
Max. temperature:
RoHS-compliant:

ICT / FCT (in-circuit test and function test)
Rotating test probes
GKS-713
4.5 mm [177 mil]
Post
Yes
Plug-in
No
Plug
No
No
No
No
SE-503
KS-713
-100 °C [-148 °F]
200 °C [392 °F]
Yes

Tip style data

Tip style:
Tip diameter:
Tip style surface:
Tip style material:

06 serrated
4 mm [.157 in]
R rhodium
2 steel

Electrical data

Current load capacity / rated current:
Current rating, connection on plunger:
Typical resistance (Ri):
Typical resistance (Ri), connection on plunger:

5 A
8 A
100 mOhm
10 mOhm

Mechanical data

Total length:
Barrel diameter:
Maximum stroke:
Spring pre-load:
Collar height:
Spring force at working stroke:
Recommended working stroke:

45 mm [1.77 in]
2.65 mm [.104 in]
5 mm [.196 in]
1.25 N [4.49 ozf]
7
5 N [17.9 ozf]
4 mm [.157 in]

Test Probe


GKS-713 206 400 R 5007

Item GKS-713-0006



ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 11/25_GB

Learn more about
ICT/FCT Test probes



ingun.com

ICT/FCT TEST PROBES