

Test Probe GKS-003 206 254 A 1200


Item GKS-003-0003



GO TO PRODUCT

ingun[®]
Partner for Future Technology

- Robust, compact design for harsh ICT/FCT applications with limited space
- For optimum contact at the test points (e.g. pads, vias, and pins), various tip styles in different diameters and finishes, as well as various spring forces are available. spring forces.



General data

Product group: ICT / FCT (in-circuit test and function test)
Sub-product group: Short/robust GKS
Series: GKS-003
Grid: 3.18 mm [125 mil]
Contacting from: Post
Magnetic: Yes
Installation type: Plug-in
Quick-exchange system: Yes
Adjustable installation height: No
Non-rotating: No
Compatible receptacle(s): KS-003
Min. temperature: -40 °C [-40 °F]
Max. temperature: 80 °C [176 °F]
RoHS-compliant: Yes

Tip style data

Tip style: 06 serrated
Tip diameter: 2.54 mm [.1 in]
Tip style surface: A gold
Tip style material: 2 steel

Electrical data

Current load capacity / rated current: 5 A
Typical resistance (R_i): 20 mOhm

Mechanical data

Total length: 33.1 mm [1.3 in]
Barrel diameter: 2.03 mm [.079 in]
Maximum stroke: 6.35 mm [.25 in]
Spring pre-load: 0.49 N [1.76 ozf]
Collar height: 00
Spring force at working stroke: 1.2 N [4.31 ozf]
Recommended working stroke: 4.4 mm [.173 in]


Test Probe GKS-003 206 254 A 1200

Item GKS-003-0003



GO TO PRODUCT

ingun[®]
Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 12/25_GB

2 / 2

Learn more about
ICT/FCT Test probes



ingun.com