




- USB-A HSD connector for HSD interface block SB-P-HSD-005 on the DUT side
- Reliable transmission of USB-A 3.1 signals
- HSD signal transmission via an interface (serial additional HSD interface blocks not yet possible)
- A USB-A 3.1 channel for signal transmission
- Signal connection with commercially available USB-A cables (e.g. USB-A to USB-A, USB-A to RJ45)
- Colour-coded assignment of the HSD connectors, blue for HSD interface block on the DUT side
- Consistently stable signal quality throughout
- Gross data rate up to 5 Gbits/s
- PoE (power over Ethernet) compatible, in accordance with IEEE 802.3

NEW



Delivery

The USB-A HSD connector is delivered fully equipped, prepared for connecting standard USB-A cables, including installation accessories.

Note:

Commercially available USB-A cables (e.g. USB-A to USB-A, USB-A to RJ45) must be purchased separately.

Note:



Number of cycles: approx. 5000

Note:

Typical insertion/extraction interface block: approx. 5 to 20 N

Application

The USB-A HSD connector is used for the reliable transmission of USB-A signals with a gross data rate of up to 5 Gbps. It has a USB-A 3.1 channel for signal transmission. The signal connection to the DUT is made using standard USB-A cables (e.g. USB-A to USB-A, USB-A to RJ45).



General data





Product group:	Electric accessory
Series:	STV
Type:	HSD-SB connector
Version:	USB-A (DUT side)
Accessory type:	Customising accessories
Scope of delivery:	Includes installation accessories
Component assembly:	
Colour:	Blue
Width:	25.4 mm [1 in]
Height:	7 mm [.275 in]
Weight:	0.01 kg [.022 lbs]
Min. temperature:	10 °C [50 °F]
Max. temperature:	60 °C [140 °F]
RoHS-compliant:	Yes

Compatible with

Interface blocks (SB):	SB-P-HSD-005
------------------------	--------------

Technical data

Connection:	USB-A 3.0 socket
Installation:	Screw M2
Number of poles:	1
Gross data rate:	5 Gbit/s
Length:	28.5 mm [1.12 in]
Outer dimensionS (WxDxH):	28.5 x 25.4 x 7 mm [1.12 x 1 x .275 in]



HSD interface blocks

Part no.	Designation	Version
116155	SB-P-HSD-005	HSD interface block for DUT side with five high-speed slots

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

