

Receptacle

KS-100 47

Item KS-10047




GO TO PRODUCT


ingun[®]

Partner for Future Technology

INGUN SELECTION



1:1



General data

Product group: Receptacles (KS)
Series: KS-100
Sub-series: KS-100 press-in version
Type of receptacle connection: Wire-wrap
Press ring: No
Surface area: Gold
Collar diameter: 1.8 mm [.07 in]
Collar height: 5.5 mm [.216 in]
Wire-wrap post length: 9.3 mm [.366 in]
Knurl: No
Vacuum-tight: yes (< 1 ccm / min)
RoHS-compliant: Yes

Mechanical data

Total length: 36.8 mm [1.44 in]
Outer diameter: 1.67 mm [.065 in]

Mounting hole

Mounting hole in CEM1: 1.68 – 1.69 mm [.066 – .066 in]
Mounting hole in FR4: 1.69 – 1.7 mm [.066 – .066 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 04/26_GB

Learn more about
Test probes



ingun.com