

Electric LED analyser ELA-06-FEASA-I-OH3

Item 34812




GO TO PRODUCT

ingun[®]
Partner for Future Technology

- FEASA(TM) LED analyser
- Testing of several LEDs simultaneously for colour and brightness



Application

The FEASA(TM) LED Analyser is used to test several LEDs simultaneously for colour and brightness. The speed of the test depends on the intensity of the LEDs being tested, i.e. bright LEDs have a shorter test time, while weaker LEDs have a longer test time.



Interface

Connection via the serial RS232 interface requires an additional power supply.



General data

Product group:

Series:

Type:

Version:

Accessory type:

Width:

Height:

Weight:

Min. temperature:

Max. temperature:

RoHS-compliant:

Electric accessory

ELA

Feasa-I (without housing)

Incl. 6x OH-3

Customising accessories

30 mm [1.18 in]

33 mm [1.29 in]

0.05 kg [.11 lbs]

0 °C [32 °F]

50 °C [122 °F]

Yes

Compatible with

Manual test fixtures (MA):

MA 2012

VA 3070

Vacuum test fixtures (VA):

ATS MAXX

MA exchangeable kits (ATS MA):

ATS PAZxxx

PA exchangeable kits (ATS PA):

Technical data

Connection: RS232

Max. current: .2 A

Max. voltage: 5,0 V

Number of poles: 6

Length: 100 mm [3.93 in]

Cable length: 600 mm [23.6 in]

Fibre optic cladding diameter: 1 mm [.039 in]

Outer dimensions (WxDxH): 100 x 30 x 33 mm [3.93 x 1.18 x 1.29 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162

78467, Constance, Germany

Phone +49 7531 8105-0

Customer hotline +49 7531 8105-888

Fax +49 7531 8105-65

info@ingun.com

