# High-Frequency Probe HFS-440 201 051 A 5002

Item HFS-440-0066





- short standard series
- Up to 4 GHz
- Cable interface MCX
- Plug-in version
- Receptacles: KS-410, KS-410 f









Ø0.51[.020]

2[.079]









### **General** data

Product group:	HFS radio-frequency test probes
Series:	HFS-440
Sub-series:	HFS-440 short version
Grid:	5.8 mm [228 mil]
DUT / contact:	PCB coax, closed
Installation type:	Plug-in
Floating mount:	No
Non-rotating:	Yes
Continuous plunger:	Yes
Interface of compatible assembly:	MCX 50 Ohm
Compatible assembly interface gender	: M signal conductor male / pin
KS sub-series:	KS-410, press-in version
Min. temperature:	-40 °C [-40 °F]
Max temperature:	80 °C [176 °F]

## **Electrical data**

Yes

Frequency range up to:	4 GHz
Impedance:	50 Ohm

#### Outer conductor data

RoHS-compliant:

Outer conductor tip style:	02 flat
Outer conductor tip style diameter:	2.6 mm [.102 in]
Spring force of entire outer conductor at working stroke	e: 4 N [14.3 ozf]
Outer conductor working stroke:	2 mm [.078 in]
Outer conductor maximum stroke:	3 mm [.118 in]
Exchangeable outer conductor:	KO-810-0150
Outer conductor max. current load capacity:	10 A

#### **Mechanical** data

Total spring force at working stroke:	5 N [17.9 ozf]
Total length:	29.7 mm [1.16 in]
Barrel diameter:	4.5 mm [.177 in]
Installation height without receptacle:	11.5 mm [.452 in]

## **INGUN** Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com









Learn more about Radio-frequency test probes

