

Reinforcement set FB-VSL-KIT-KTE-ATSMA12

Item 45719




GO TO PRODUCT

ingun[®]
Partner for Future Technology

- To be installed under the probe plate (KTP)
- Recommended for customisations with more than 300 test probes or a force greater than 500 N
- The scope of delivery includes one strip with fixing material in each case

Application

For reinforcing the probe plate (KTP) to prevent deflection due to high forces resulting from customisation.



General data

Product group:
Series:
Type:
Version:
Accessory type:
Scope of delivery:
Material:
Width:
Height:
Weight:
Min. temperature:
Max. temperature:
RoHS-compliant:

Functional units
FB-ATSMAXx
Reinforcement bar for probe plate (KTP)
Set including installation accessories
Additional function
1 x reinforcement bar
1.0037, galvanised
10 mm [.393 in]
60 mm [2.36 in]
0.5 kg [1.1 lbs]
10 °C [50 °F]
60 °C [140 °F]
Yes

Compatible with

Exchangeable kits version:
MA exchangeable kits (ATS MA):

No RF
ATS MA12

Technical data

Length:
Outer dimensions (WxDxH): 10 x 284 x 60 mm [.393 x 11.1 x 2.36 in]

Reinforcement set

FB-VSL-KIT-KTE-ATSMA12


Item 45719



GO TO PRODUCT

ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162

78467, Constance, Germany

Phone +49 7531 8105-0

Customer hotline +49 7531 8105-888

Fax +49 7531 8105-65

info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 12/25_GB

2 / 2

Learn more about
MA functional units



ingun.com

FUNCTIONAL UNIT