




GO TO PRODUCT



### General data

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| Product group:                  | ICT / FCT (in-circuit test and function test) |
| Sub-product group:              | INGUN E-TYPE®                                 |
| Series:                         | E-135                                         |
| Grid:                           | 2.54 mm [100 mil]                             |
| Contacting from:                | Via                                           |
| Magnetic:                       | Yes                                           |
| Installation type:              | Plug-in                                       |
| Quick-exchange system:          | Yes                                           |
| Adjustable installation height: | No                                            |
| Non-rotating:                   | No                                            |
| Compatible receptacle(s):       | KS-100                                        |
| Min. temperature:               | -40 °C [-40 °F]                               |
| Max. temperature:               | 80 °C [176 °F]                                |
| RoHS-compliant:                 | Yes                                           |

### Tip style data

|                     |                          |
|---------------------|--------------------------|
| Tip style:          | 91 dagger, self-cleaning |
| Tip diameter:       | 0.9 mm [.035 in]         |
| Tip style surface:  | E palladium / nickel     |
| Tip style material: | 2 steel                  |

### Electrical data

|                                        |         |
|----------------------------------------|---------|
| Current load capacity / rated current: | 5 A     |
| Typical resistance (Ri):               | 30 mOhm |

### Mechanical data

|                                 |                   |
|---------------------------------|-------------------|
| Total length:                   | 38.7 mm [1.52 in] |
| Barrel diameter:                | 1.37 mm [.053 in] |
| Maximum stroke:                 | 11.5 mm [.452 in] |
| Spring pre-load:                | 0.78 N [2.8 ozf]  |
| Collar height:                  | 00                |
| Spring force at working stroke: | 2.8 N [10 ozf]    |
| Recommended working stroke:     | 9.3 mm [.366 in]  |

# Test Probe INGUN E-Type


## E-135 291 090 E 2800

Item E-135-0006



**ingun**<sup>®</sup>

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 12/25\_GB

Learn more about  
ICT/FCT Test probes



ingun.com

ICT/FCT TEST PROBES