

Electric LED analyser ELA-10-FEASA-F-OH3

Item 31211




GO TO PRODUCT

ingun[®]
Partner for Future Technology

- FEASA(TM) LED analyser
- Testing of several LEDs simultaneously for colour and brightness



Application

The FEASA(TM) LED Analyser is used to test several LEDs simultaneously for colour and brightness. The speed of the test depends on the intensity of the LEDs being tested, i.e. bright LEDs have a shorter test time, while weaker LEDs have a longer test time.



Interface

Connection via the serial RS232 interface requires an additional power supply, connection via the USB interface does not require an additional power supply.



General data

Product group:

Series:

Type:

Version:

Accessory type:

Width:

Height:

Weight:

Min. temperature:

Max. temperature:

RoHS-compliant:

Electric accessory

ELA

Feasa-F (with housing)

Incl. 10x OH-3

Customising accessories

54 mm [2.12 in]

39 mm [1.53 in]

0.09 kg [.198 lbs]

0 °C [32 °F]

50 °C [122 °F]

Yes

Compatible with

Manual test fixtures (MA):

MA 2012

Vacuum test fixtures (VA):

VA 3070

MA exchangeable kits (ATS MA):

ATS MAXX

PA exchangeable kits (ATS PA):

ATS PAZXXX

Technical data

Connection: USB & RS232

.2 A

Max. current: 5,0 V

Max. voltage: 10

Number of poles: 104 mm [4.09 in]

Length: 600 mm [23.6 in]

Cable length: 1 mm [.039 in]

Fibre optic cladding diameter: 104 x 54 x 39 mm [4.09 x 2.12 x 1.53 in]

Outer dimensionS (WxDxH):

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162

78467, Constance, Germany

Phone +49 7531 8105-0

Customer hotline +49 7531 8105-888

Fax +49 7531 8105-65

info@ingun.com

